

Technical Data


14 x 125mm T&G Engineered Oak

Cashmere Grey: Brushed & Matt Lacquered | ENG-OAK-1403

Product Photo:



Board Construction:



Product Specification & Handling Information:

Board Depth:	14mm
Board Width:	125mm
Board Length:	Random Lengths (300-1200mm)
Pack Size:	1.80m ²
Pack Weight:	17kg
Packs Per Pallet:	48

Manufacturer Testing Standard:

Standard:	EN14342:2013 - Multi-layer Flooring Board
Reaction to Fire:	Dfl - s1
Minimum Density:	650 kg/m ³
Minimum Thickness:	14mm
Formaldehyde:	E-1
Thermal Conductivity:	0.16 W/mK

Board Detail:

Type of Board:	Engineered Wood Flooring
Finish:	Brushed & Oiled
Bevel Detail:	4V Bevel
Density of Finish:	NPD
Fix System:	T&G
Grade:	Rustic
Core Material:	Eucalyptus & Poplar
Janka Reading:	1360

Misc Items:

Residential Warranty:	15 Years
Commercial Warranty:	On Request
Oak Origin:	Europe
Manufactured In:	PRC
Installation Type:	<input checked="" type="checkbox"/> Float
	<input checked="" type="checkbox"/> Bond
	<input checked="" type="checkbox"/> Nail
Underfloor Heating:	Suitable for UFH if installed as floating floor with DPM underlay. - Manifold temp must not exceed 26°C

Key Features:



Accreditations:

